

Application Serial No. 09/874,574

1. (Currently Amended) A computer-implemented method comprising:  
identifying a plurality of data signatures relevant to computer security;  
designating an alert condition value to each data signature based on each data signature itself and contextual information associated with the data signature, the contextual information comprising at least one of an application layer data field type used to encapsulate the data signature and an application layer protocol type used to transmit the data signature, the alert condition value indicating a security risk level relative to different data signatures and relative to other identical data signatures associated with different contextual information;

creating a table comprising the contextual information, the data signatures, and the alert condition values;

detecting a data signature by evaluating communications at an application layer level between a target and a suspect;

correlating said data signature with an application layer fingerprint of the target to determine to what extent said target is vulnerable to said data signature;

evaluating contextual information related to the data signature by comparing the contextual information and the data signature to the table in order to determine a likelihood that said target is under attack, the contextual information comprising at least one of an application layer data field type used to encapsulate the data signature and an application layer protocol type used to transmit the data signature; and

assigning an alert condition value to the data signature based on the comparison of the contextual information and data signature to data in the table.

2. (Cancelled).

3. (Original) The method as in Claim 1 wherein said fingerprint includes said target node's operating system version.

4. (Original) The method as in Claim 1 wherein said fingerprint includes said target node's processor type.

5. (Cancelled).

Application Serial No. 09/874,574

6. (Original) The method as in Claim 1 further comprising:  
generating a first alert condition upon determining that said target node is  
vulnerable to said data signature.
7. (Original) The method as in Claim 1 further comprising:  
listening for a response to said data signature from said target.
8. (Original) The method as in Claim 7 further comprising:  
determining whether said target node's response or lack of a response is  
suspicious.
9. (Original) The method as in Claim 8 wherein determining whether said  
target's response is suspicious comprises determining whether said target's response is an  
"unknown command" response.
10. (Original) The method as in Claim 8 further comprising:  
generating a second alert condition upon determining that said target node's  
response or lack of a response is suspicious
11. (Original) The method as in Claim 10 further comprising:  
combining the second alert with the first, thereby updating the first alert with  
information within the second alert.
12. (Original) The method as in Claim 1 further comprising:  
listening for behavior of said target node; and  
generating a second alert condition upon determining that said target node's  
behavior is suspicious.
13. (Original) The method as in Claim 11 wherein said target node's suspicious  
behavior comprises transmitting a root shell prompt to a suspect node.

Application Serial No. 09/874,574

14. (Currently Amended) A computer-implemented method comprising:

identifying a plurality of data signatures relevant to computer security;

designating an alert condition value to each data signature based on each data signature itself and contextual information associated with the data signature, the contextual information comprising at least one of an application layer data field type used to encapsulate the data signature and an application layer protocol type used to transmit the data signature, the alert condition value indicating a security risk level relative to different data signatures and relative to other identical data signatures associated with different contextual information;

creating a table comprising the data signatures, contextual information, and alert condition values provided in context;

identifying a data signature encapsulated in an application layer data field and directed at a target using an application layer protocol;

evaluating a context of the data signature by one of:

reviewing the application layer data field type;

reviewing the application layer protocol type;

comparing the evaluated context of the data signature to the table;

determining whether said data signature poses a threat based on said context of said data signature; and

assigning an alert condition value to the data signature based on the comparison of the context to data in the table.

15. (Cancelled.)

16. (Previously Presented) The method as in Claim 14 wherein said protocol is the HyperText Transport Protocol ("HTTP").

17. (Original) The method as in Claim 16 further comprising:

determining that said data signature poses a threat if said data signature is "/cgi-bin/php" embedded in the header of said HTTP data transmission.

Application Serial No. 09/874,574

18. (Original) The method as in Claim 14 further comprising evaluating whether said data signature poses a threat based on a fingerprint of said target.

19. (Original) The method as in Claim 18 wherein said fingerprint is comprised of a particular service executed on said target.

20. (Original) The method as in Claim 18 wherein said fingerprint is comprised of a particular operating system executed on said target.

21. (Original) The method as in Claim 18 wherein said fingerprint is comprised of a particular hardware platform of said target.

22. (Original) The method as in Claim 14 further comprising:  
monitoring responses from said target following said data signature; and  
determining a likelihood of whether said target is under attack based on data signatures of said responses.

23. (Original) The method as in Claim 22 wherein said target response is a non-protocol response.

24. (Original) The method as in Claim 23 wherein said data signature is transmitted to the target using the file transfer protocol ("FTP") and said non-protocol response indicates a raw shell connection to said target.

[The remainder of this page has been intentionally left blank.]

Application Serial No. 09/874,574

25. (Currently Amended) A computer-implemented method comprising:

identifying a plurality of data signatures relevant to computer security;

designating a relative alert condition value to each data signature based on each data signature itself and contextual information associated with the data signature, the contextual information comprising at least one of an application layer data field type used to encapsulate the data signature and an application layer protocol type used to transmit the data signature, the alert condition value indicating a security risk level relative to different data signatures and relative to other identical data signatures associated with different contextual information;

creating a table comprising the contextual information, the data signatures, and the relative alert condition values;

monitoring a plurality of data transmissions at an applications layer level between a suspect and a target to identify one or more data signatures, said data transmissions indicating a current state of communication between said suspect and said target;

evaluating contextual information related to each data signature by comparing the contextual information and data signatures to the table, ~~the contextual information comprising at least one of an application layer data field type used to encapsulate a respective data signature and an application layer protocol type used to transmit a respective data signature;~~

evaluating a likelihood that said target is under attack based on the contextual information of one or more data signatures of said transmissions and said current state of communication; and

assigning a relative alert condition value to the data signature based on the comparison of the contextual information to data in the table.

26. (Original) The method as in Claim 25 wherein said current state of communication is based on a known protocol with which said data transmissions are transmitted/received between said suspect and target.

27. (Original) The method as in Claim 26 wherein said known protocol is FTP.

28. (Original) The method as in Claim 27 wherein one of said data signatures is the filename "passwd" in a context in which filenames are likely to appear.

Application Serial No. 09/874,574

29. (Original) The method as in Claim 25 further comprising:  
monitoring responses from said target following said data signature; and  
determining a likelihood of whether said target is under attack based on data signatures of said responses.

30. (Original) The method as in Claim 25 wherein said current state comprises  
any outbound connection from said target is following a detected signature.

31. (Original) The method as in Claim 25 wherein said current state comprises  
an inbound connection to a new port following a detected signature.

32. (Previously Presented) The method as in Claim 25 monitoring said current  
state comprises:

profiling said target to determine which ports are open by passively listening to  
what traffic succeeds in talking to/from the target.

33. (Previously Presented) The method as in Claim 25 monitoring said current  
state comprises:

detecting non-protocol requests or responses transmitted to/from said target.

34. (Original) The method as in Claim 25 further comprising:  
determining a fingerprint of said target; and  
further evaluating a likelihood that said target is under attack based on said  
fingerprint.

35. (Original) The method as in Claim 26 wherein said known protocol is HTTP

36. (Original) The method as in Claim 26 wherein said known protocol is RPC.

Application Serial No. 09/874,574

37. (Currently Amended) A machine-readable medium having program code stored thereon which, when executed by a machine, causes said machine to perform the operations of:

identifying a plurality of data signatures relevant to computer security;

designating a relative alert condition value to each data signature based on each data signature itself and contextual information associated with the data signature, the contextual information comprising at least one of an application layer data field type used to encapsulate the data signature and an application layer protocol type used to transmit the data signature, the relative alert condition value indicating a security risk level relative to different data signatures and relative to other identical data signatures associated with different contextual information;

creating a table comprising the contextual information, the data signatures, and the relative alert condition values;

detecting a data signature by evaluating communications at an application layer level between a target and a suspect;

correlating said data signature with a fingerprint of the target to determine to what extent said target is vulnerable to said data signature; and

evaluating contextual information related to the data signature by comparing the contextual information and the data signature to the table in order to determine a likelihood that said target is under attack, ~~the contextual information comprising at least one of an application layer data field type used to encapsulate the data signature and an application layer protocol type used to transmit the data signature;~~ and

assigning a  $a[n]$  relative alert condition value to the data signature based on the comparison of the contextual information and data signature to data in the table.

38. (Original) The machine-readable medium as in Claim 37 further comprising program code to cause said machine to perform the operations of:

evaluating contextual information related to said data signature to determine a likelihood that said target is under attack.

39. (Original) The machine-readable medium as in Claim 37 wherein said fingerprint includes said target node's operating system version.

Application Serial No. 09/874,574

40. (Original) The machine-readable medium as in Claim 37 wherein said fingerprint includes said target node's processor type.

41. (Cancelled.)

42. (Original) The machine-readable medium as in Claim 37 further comprising program code to cause said machine to perform the operations of:

generating a first alert condition upon determining that said target node is vulnerable to said data signature.

43. (Original) The machine-readable medium as in Claim 37 further comprising program code to cause said machine to perform the operations of:

listening for a response to said data signature from said target.

44. (Original) The machine-readable medium as in Claim 43 further comprising program code to cause said machine to perform the operations of:

determining whether said target node's response or lack of a response is suspicious.

45. (Original) The machine-readable medium as in Claim 44 wherein determining whether said target's response is suspicious comprises determining whether said target's response is an "unknown command" response.

46. (Original) The machine-readable medium as in Claim 44 further comprising program code to cause said machine to perform the operations of:

generating a second alert condition upon determining that said target node's response or lack of a response is suspicious



Application Serial No. 09/874,574

47. (Original) The machine-readable medium as in Claim 46 further comprising program code to cause said machine to perform the operations of:

combining the second alert with the first, thereby updating the first alert with information within the second alert.

48. (Original) The machine-readable medium as in Claim 37 further comprising program code to cause said machine to perform the operations of:

listening for behavior of said target node; and

generating a second alert condition upon determining that said target node's behavior is suspicious.

49. (Original) The machine-readable medium as in Claim 47 wherein said target node's suspicious behavior comprises transmitting a root shell prompt to a suspect node.

[The remainder of this page has been intentionally left blank.]

Application Serial No. 09/874,574

50. (Currently Amended) A machine-readable medium having program code stored thereon which, when executed by a machine, causes said machine to perform the operations of:

identifying a plurality of data signatures relevant to computer security;

designating an alert condition value to each data signature based on each data signature itself and contextual information associated with the data signature, the contextual information comprising at least one of an application layer data field type used to encapsulate the data signature and an application layer protocol type used to transmit the data signature, the alert condition value indicating a security risk level relative to different data signatures and relative to other identical data signatures associated with different contextual information;

creating a table comprising the data signatures, the contextual information, and the alert condition values provided in context;

identifying a data signature encapsulated in an application layer data field directed at a target using an application layer protocol;

evaluating a context of the data signature by one of:

reviewing the application layer data field type;

reviewing the application layer protocol type; and

comparing the evaluated context of the data signature to the table;

determining whether said data signature poses a threat based on said context of said data signature; and

assigning an alert condition value to the data signature based on the comparison of the context to data in the table.

51. (Cancelled.)

52. (Previously Presented) The machine-readable medium as in Claim 50 wherein said protocol is the HyperText Transport Protocol ("HTTP").

Application Serial No. 09/874,574

53. (Original) The machine-readable medium as in Claim 52 further comprising program code to cause said machine to perform the operations of:

determining that said data signature poses a threat if said data signature is "Icgi-bin/phf" embedded in the header of said HTTP data transmission.

54. (Original) The machine-readable medium as in Claim 50 further comprising program code to cause said machine to perform the operations of:

further evaluating whether said data signature poses a threat based on a fingerprint of said target.

55. (Original) The machine-readable medium as in Claim 54 wherein said fingerprint is comprised of a particular service executed on said target.

[The remainder of this page has been intentionally left blank.]

Application Serial No. 09/874,574

56. (Currently Amended) A machine-readable medium having program code stored thereon which, when executed by a machine, causes said machine to perform the operations of:

identifying a plurality of data signatures relevant to computer security;

designating a relative alert condition value to each data signature based on each data signature itself and contextual information associated with the data signature, the contextual information comprising at least one of an application layer data field type used to encapsulate the data signature and an application layer protocol type used to transmit the data signature, the relative alert condition value indicating a security risk level relative to different data signatures and relative to other identical data signatures associated with different contextual information;

creating a table comprising the contextual information, the data signatures, and the relative alert condition values;

monitoring a plurality of data transmissions at an applications layer level between a suspect and a target to identify one or more data signatures, said data transmissions indicating a current state of communication between said suspect and said target;

evaluating contextual information related to each data signature by comparing the contextual information and data signatures to the table, ~~the contextual information comprising at least one of an application layer data field type used to encapsulate a respective data signature and an application layer protocol type used to transmit a respective data signature;~~

evaluating a likelihood that said target is under attack based on the contextual information of one or more data signatures of said transmissions and said current state of communication; and

assigning a relative alert condition value to the data signature based on the comparison of the contextual information to data in the table.

57. (Original) The machine-readable medium as in Claim 56 comprising program code to cause said machine to perform the additional operations of:

monitoring responses from said target following said data signature; and

determining a likelihood of whether said target is under attack based on data signatures of said responses.